

Certificate of Transmission Under 37 CFR1.8

I hereby certify that this correspondence is
being facsimile transmitted to the U. S. Patent
and Trademark Office (Fax. 00915712738300) on

Nov. 23, 2005

Date

Tsung-Yen Tsai

Name

Signature

Tsung-Yen Tsai

~~This copy is also mailed to USPTO at the same time~~

RECEIVED
CENTRAL FAX CENTER

NOV 23 2005

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant Tsung-Yen Tsai Art Unit: 2835

Series No 10/634,674 Examiner: DUONG, IIUNG Y

Filed 08/06/2003

Title HEAT DISSIPATING DEVICE OF POWER SUPPLY

Mail Stop Non-Fee Amendment

Honorable Assistant Commissioner for Patents

P.O. Box 1450

Alexandria, VA 22313-1450

Dear Sir:

Attached is a check of 60 U. S. dollars as an extension fee for one month
delay to respond the office action.

Responsive to the Official Action date 07 / 26 / 2005, please amend the above-referenced Patent Application as following:

AMENDMENT

IN THE SPECIFICATION

Please amend the second paragraph of the detailed description of the invention as the following. The added part is based on Fig. 2 of the present invention. Thereby it is assured that no new matter is added.

With reference to Figs. 2 and 4, the heat dissipating device of a power supply of the present invention is illustrated. The power supply 1 is installed at a rear side of a computer. The power supply 1 includes a base 11, and a cover 12. Power is conducted into a receptacle 13 at a back side of the base 11. The voltage of the power is reduced by an electric element 14 and then is supplied to the computer. The feature of the present invention is that an upper end of the cover 12 is formed with a through hole 121 the size of which is expanded as large as possible in the upper end of the cover 12. A fan 122 is installed in an interior of the through hole 121. A mask 123 covers upon the through hole 121 for avoiding undesired object to enter into the through hole 121. The fan 122 can sense the temperature of the power supply 1 and the rotation speed of the fan 122 is adjustable for sucking outer cool air (referring to Fig. 4) to blow the interior electronic element 14. The air is vented out from the plurality of ventilating holes 110 at the back side of the base 11, a plurality of long straight holes arranged at a side of the base opposite to the backside side having the hexagonal ventilating holes 11, and a plurality of long straight hole in each of the two opposite sides of the cover.